GENTECH
SOUTH AFRICA PTY LTD
POWER SOLUTIONS

GenTech SA (Pty) Ltd
010 012 6020
sales@gentechsa.co.za
126 Birch Road, corner Larch Road
Benoni AH, Benoni, 1501

1500 kVA Cummins PRIME SOUND ATTENUATED CANOPY DIESEL GENERATOR



SOUND ATTENUATED	LOAD TESTED	GENTECH SUPPORT
SMARTGEN CONTROL	ATS / AMF INCLUDED	AVR REGULATION

About Cummins

Cummins diesel engines are widely used in power-generation applications. GenTech SA can configure Cummins-powered generator sets for standby, commercial and industrial requirements with SmartGen control and automatic mains-failure operation.

GenTech SA configures the 1500 kVA Cummins generator with SmartGen automatic control, an AVR-regulated brushless alternator, ATS / automatic mains-failure changeover included as standard, a GenTech canopy-based fuel system and a sound-attenuated enclosure configuration for reliable power in demanding environments.

GENTECH
SOUTH AFRICA PTY LTD
POWER SOLUTIONS

GenTech SA (Pty) Ltd
010 012 6020
sales@gentechsa.co.za
126 Birch Road, corner Larch Road
Benoni AH, Benoni, 1501

ENGINE SPECIFICATIONS

CUMMINS KTA50-GS8

Cummins engine platform

Engine output shown using the Prime Power (PRP) reference for the 1500 kVA GenTech build.

SPECIFICATION	DETAIL
Engine manufacturer	Cummins
Engine model	CUMMINS KTA50-GS8
Displacement	50.3 L
Cylinder bore / stroke	159 × 159 mm
Fuel system	Cummins PT direct injection
Cylinders	16
Cylinder arrangement	60° Vee
Engine output @ 1500 rpm	1287 kW PRP
Aspiration	Turbocharged & low-temperature aftercooled
Cycle	4-stroke diesel
Compression ratio	Not stated in supplied Cummins sheet
Fuel tank capacity	1000 L
Fuel consumption @ 100% load	309 L/h
Fuel consumption @ 75% load	238 L/h
Fuel consumption @ 50% load	167 L/h
Fuel consumption @ 25% load	88 L/h
Recommended oil type	15W40
Oil capacity	178 L
Cooling method	Two-loop cooling system
Coolant capacity	348 L
Starter system	24 V
Governor system	Not stated in supplied Cummins sheet
Engine speed	1500 RPM

Product images are representative and specifications may change without notice.

GENTECH
SOUTH AFRICA PTY LTD
POWER SOLUTIONS

GenTech SA (Pty) Ltd
010 012 6020
sales@gentechsa.co.za
126 Birch Road, corner Larch Road
Benoni AH, Benoni, 1501

1 ALTERNATOR & ELECTRICAL SPECIFICATIONS



Generator output class	1500 kVA
Standard alternator	Faraday / Werna or equivalent quality
Premium alternator options	Mecc Alte / Leroy-Somer - quoted on request
Alternator type	Brushless
Phase configuration	Three phase
Rated voltage	380–400 V
Rated frequency	50 Hz
Speed	1500 RPM
Automatic Voltage Regulator	AVR included
Protection class	IP23

2 SMARTGEN CONTROL SYSTEM



The SmartGen automatic controller provides comprehensive monitoring and control of the generator set, including automatic start/stop, protection, alarm indication and operating data display. It is suitable for mains-failure backup and solar-ready applications, supporting reliable and unattended operation.

Controller	SmartGen automatic generator controller
ATS / automatic changeover	Included as standard

3 WARRANTY, SERVICE & OPERATING NOTES

Mechanical warranty	1 year / 1,000 hours, whichever occurs first, subject to GenTech SA terms and conditions
First service	50 hours / 3 months, whichever occurs first
Second service	200 hours / 6 months, whichever occurs first
Third service	550 hours / 12 months, whichever occurs first
Ongoing service	Annually or at the applicable engine manufacturer interval, whichever occurs first

OPERATING NOTES

Prime Power (PRP) is intended for long-running applications where the electrical load changes. Continuous / Base Load (COP) applies where the generator carries a steady or sustained load. Actual available output can be affected by altitude, ambient temperature, ventilation, power factor and the type of electrical load. Heavy sustained PF 1.0-type loads may require additional generator capacity. Full GenTech SA warranty and operating conditions apply.