


300 kVA FAW PRIME SOUND ATTENUATED CANOPY DIESEL GENERATOR



SOUND ATTENUATED

LOAD TESTED

GENTECH SUPPORT

SMARTGEN CONTROL

ATS / AMF INCLUDED

AVR REGULATION

About FAWDE

FAWDE (FAW Wuxi Diesel Engine Works) is a long-established diesel-engine manufacturer within the FAW Group. Its engines are widely used in generator, industrial and commercial applications, with a reputation for practical performance, parts support and dependable operation.

GenTech SA configures the 300 kVA FAW generator with SmartGen automatic control, an AVR-regulated brushless alternator, ATS / automatic mains-failure changeover included as standard, a GenTech canopy-based fuel system and a sound-attenuated enclosure configuration for reliable power in demanding environments.

ENGINE SPECIFICATIONS

To be confirmed



FAW engine platform

Engine output shown using the Prime Power (PRP) reference for the 300 kVA GenTech build.

SPECIFICATION	DETAIL
Engine manufacturer	FAW
Engine model	To be confirmed
Displacement	To be confirmed
Cylinder bore / stroke	To be confirmed
Cylinders	6-cylinder, vertical inline
Engine output @ 1500 rpm	To be confirmed
Cycle	4-stroke diesel
Fuel tank capacity	400 L
Fuel consumption @ 100% load	To be confirmed
Fuel consumption @ 75% load	To be confirmed
Fuel consumption @ 50% load	To be confirmed
Recommended oil type	15W40
Oil capacity	To be confirmed
Cooling method	Water cooled
Coolant capacity	To be confirmed
Starter system	24 V
Governor system	Electronic
Engine speed	1500 RPM

1 ALTERNATOR & ELECTRICAL SPECIFICATIONS



Generator output class	300 kVA
Standard alternator	Faraday / Werna or equivalent quality
Premium alternator options	Mecc Alte / Leroy-Somer - quoted on request
Alternator type	Brushless
Phase configuration	Three phase
Rated voltage	380–400 V
Rated frequency	50 Hz
Speed	1500 RPM
Automatic Voltage Regulator	AVR included
Protection class	IP23

2 SMARTGEN CONTROL SYSTEM



The SmartGen automatic controller provides comprehensive monitoring and control of the generator set, including automatic start/stop, protection, alarm indication and operating data display. It is suitable for mains-failure backup and solar-ready applications, supporting reliable and unattended operation.

Controller	SmartGen automatic generator controller
ATS / automatic changeover	Included as standard

3 WARRANTY, SERVICE & OPERATING NOTES

Mechanical warranty	1 year / 1,000 hours, whichever occurs first, subject to GenTech SA terms and conditions
First service	50 hours / 3 months, whichever occurs first
Second service	200 hours / 6 months, whichever occurs first
Third service	550 hours / 12 months, whichever occurs first
Ongoing service	Annually or at the applicable engine manufacturer interval, whichever occurs first

OPERATING NOTES

Prime Power (PRP) is intended for long-running applications where the electrical load changes. Continuous / Base Load (COP) applies where the generator carries a steady or sustained load. Actual available output can be affected by altitude, ambient temperature, ventilation, power factor and the type of electrical load. Heavy sustained PF 1.0-type loads may require additional generator capacity. Full GenTech SA warranty and operating conditions apply.