

80 kVA John Deere PRIME SOUND ATTENUATED CANOPY DIESEL GENERATOR



About John Deere

John Deere industrial diesel engines are used in a wide range of power-generation applications. GenTech SA configures John Deere generator sets for standby, commercial and industrial applications where serviceability and dependable operation are important.

GenTech SA configures the 80 kVA John Deere generator with SmartGen automatic control, an AVR-regulated brushless alternator, ATS / automatic mains-failure changeover included as standard, a GenTech canopy-based fuel system and a sound-attenuated enclosure configuration for reliable power in demanding environments.

ENGINE SPECIFICATIONS

JOHN DEERE 4045TFG20 / 4045TFU20



JOHN DEERE

John Deere engine platform

Engine output shown using the Prime Power (PRP) reference for the 80 kVA GenTech build.

SPECIFICATION	DETAIL
Engine manufacturer	John Deere
Engine model	JOHN DEERE 4045TFG20 / 4045TFU20
Displacement	4.5 L
Cylinder bore / stroke	106 × 127 mm
Cylinders	4
Cylinder arrangement	In-line
Engine output @ 1500 rpm	65 kW PRP
Aspiration	Turbocharged
Cycle	4-stroke diesel
Compression ratio	17.0:1
Fuel tank capacity	300 L
Fuel consumption @ 100% load	17 L/h
Fuel consumption @ 75% load	12.9 L/h
Fuel consumption @ 50% load	8.9 L/h
Fuel consumption @ 25% load	4.9 L/h
Recommended oil type	15W40
Oil capacity	12 L
Cooling method	Water cooled
Coolant capacity	16.3 L
Starter system	3.2 kW, 12 V
Governor system	Mechanical, compatible with e-gov
Engine speed	1500 RPM

1 ALTERNATOR & ELECTRICAL SPECIFICATIONS



Generator output class	80 kVA
Standard alternator	Faraday / Werna or equivalent quality
Premium alternator options	Mecc Alte / Leroy-Somer - quoted on request
Alternator type	Brushless
Phase configuration	Three phase
Rated voltage	380–400 V
Rated frequency	50 Hz
Speed	1500 RPM
Automatic Voltage Regulator	AVR included
Protection class	IP23

2 SMARTGEN CONTROL SYSTEM



The SmartGen automatic controller provides comprehensive monitoring and control of the generator set, including automatic start/stop, protection, alarm indication and operating data display. It is suitable for mains-failure backup and solar-ready applications, supporting reliable and unattended operation.

Controller	SmartGen automatic generator controller
ATS / automatic changeover	Included as standard

3 WARRANTY, SERVICE & OPERATING NOTES

Mechanical warranty	1 year / 1,000 hours, whichever occurs first, subject to GenTech SA terms and conditions
First service	50 hours / 3 months, whichever occurs first
Second service	200 hours / 6 months, whichever occurs first
Third service	550 hours / 12 months, whichever occurs first
Ongoing service	Annually or at the applicable engine manufacturer interval, whichever occurs first

OPERATING NOTES

Prime Power (PRP) is intended for long-running applications where the electrical load changes. Continuous / Base Load (COP) applies where the generator carries a steady or sustained load. Actual available output can be affected by altitude, ambient temperature, ventilation, power factor and the type of electrical load. Heavy sustained PF 1.0-type loads may require additional generator capacity. Full GenTech SA warranty and operating conditions apply.